

RoMix

REACTIVE • HIGH PERFORMANCE



RO-396

FORM RELEASE AGENT

MULTI-USE FORM RELEASE AGENT, NON-HAZARDOUS AND NON-DOT-REGULATED. NON-STAINING, INCREASES FORM LIFE AND SAFE TO USE!

Ready
To
Use

CHARACTERISTICS:

- ★ CLEAN, POSITIVE STRIPPING
- ★ ELIMINATES BUG HOLES
- ★ NON-REGULATED
- ★ MFG. IN U.S.A.
- ★ NON-CARCINOGENIC
- ★ HIGH COVERAGE RATES
- ★ NON-STAINING
- ★ CORROSION PREVENTATIVE
- ★ NO VOC'S
- ★ NON-FREEZING
- ★ HELPS KEEP FORMS CLEAN
- ★ WORKS IN ALL TEMPERATURES
- ★ SAFE & EASY TO USE
- ★ NON HAZARDOUS

RO-396 FORM RELEASE AGENT CONTAINS AN **ACTIVE AGENT** DISSOLVED INTO A PROPRIETARY, STATE-OF-THE-ART MINERAL OIL CARRIER. **RO-396** IS SPECIALLY FORMULATED TO BE APPLIED TO CLEAN SURFACES IN A THIN FILM FOR BEST RELEASING PERFORMANCE AND ECONOMY. **RO-396** IS MOST EFFECTIVE IF SPRAYED. **RO-396** IS A READY-TO-USE PRODUCT, DILUTION IS NOT RECOMMENDED AND CAN CAUSE DIFFICULTY IN STRIPPING. **RO-396** CAN BE APPLIED MINUTES OR DAYS BEFORE A JOB.

RO-396 EXCEEDS EMISSION REQUIREMENTS FOR 40 CFR PART 59 FORM RELEASE (EPA LIMIT 450G/L). **RO-396** MEETS AND EXCEEDS VOC COMPLIANCE FOR THE STATE OF CALIFORNIA, REGULATION 8, ORGANIC COMPOUNDS, RULE 3, ARCHITECTURAL COATINGS (CA LIMIT 250G/L). **RO-396** MEETS AND EXCEEDS ALL VOC REGULATIONS BY HAVING NO VOLATILE ORGANIC COMPOUNDS (VOC) AND IS DEFINED NON-VOC BY CARB.



COVERAGE RATES

1900-2100 sq.ft./gal. - non-porous
1400-1800 sq.ft./gal. - semi-porous
800-1600 sq.ft./gal. - highly porous
*results may vary due to conditions

TYPICAL PROPERTIES:

- PHYSICAL FORM ~ GOLDEN AMBER LIQUID
- SPECIFIC GRAVITY ~ 0.893G/ML
- LBS PER GAL. ~ 7.15 • ODOR ~ NEGLIGIBLE
- FLASH POINT ~> 345F • DOT CLASSIFICATION ~ NON-REGULATED • INSOLUBLE IN WATER

✓ TEST SPOT RECOMMENDED ON RUBBER AND LATEX MOLDS.
APPROVED BY REDI-ROCK, STRONG STONE AND ULTRA BLOCK